





TECHNICAL INFORMATION

Model	HVB-A-07-500-078-036-08-3-70	HVB-A-05-350-078-036-08-3-50
Approximate Temperature	113°F - 131°F (45°C - 55°C)	149°F - 167°F (65°C - 75°C)
Blanket Dimensions	36" x 86" (91.44 cm x 218.44 cm)	36" x 86" (91.44 cm x 218.44 cm)
Element Dimensions	33" x 74" (83.82 cm x 187.96 cm)	33" x 74" (83.82 cm x 187.96 cm)
Wattage	720 Watts	800 Watts
Amps	6 Amps	7 Amps
Power	120 AC	120 AC

55 GALLON HEATED DRUM BLANKET

Neptech Inc. manufactures a custom-designed, high-quality Flexotherm[™] Heated Drum/Barrel Blanket for a multitude of industries and applications.

The Flexotherm[™] Heated Drum/Barrel blanket is suitable for a wide variety of plastic, fiber, and metal containers. The blanket offers an even and continuous heat source throughout.

FEATURES

- Outfitted with a GFCI for extra security for both the product and user
- High Efficiency Carbon Heating Grid evenly distributes heat over the entire blanket area
- Heating element, unlike others, decrease current as temperature increases
- Constructed of Heavy Duty Vinyl that is NFPA
 Certified Flame Retardant
- Blankets are outfitted with adjustable retaining straps and quick release plated buckles
- Vinyl Panel Perimeters are sealed with a fully welded seam

INDUSTRIES

- Biofuel
- Petrochemical
- Diesel Exhaust Fluids (DEF) in drums/tanks/ transportation vehicles
- Chemical
- Pharmaceutical

- Military
- Epoxy and Resins
- Food and Beverage
- Tar Dispensing
- Spray Polyurethane Foam

Copyright © 2014 Neptech Inc., Manufacturer of Flexotherm™ Products 2000 East Highland Road, Highland, MI 48357 810.225.2222 | www.neptechinc.com | www.flexotherm.net