

## HOT POCKETS



Series



Temperature



Power



Configuration



Sensor



Options

<b>Series</b>	<b>TCHP</b> - Temperature Controlled Hot Pocket <b>SCHP</b> - Slave Connection Hot Pocket		
<b>Temperature</b>	Customer Specification _____		
<b>Power</b>	<b>Voltage</b>		<b>Connector</b>
	<b>A</b> —110 / 115 / 120 VAC <b>B</b> —208 VAC <b>C</b> —220 / 230 / 240 VAC <b>D</b> —440 / 460 / 480 VAC <b>E</b> —12 VDC	<b>A</b> - 7-Pin AMP™ (Power Pins 3-5) 10Amp Max. Load <b>T</b> - Mini Twist Lock (NEMA ML2-15)* (standard) <b>M</b> - Molex 3-Pin <b>N</b> - None <b>S</b> - Custom / Special (Specify NEMA Code of Connector P/N)	
<b>Configuration</b>	<b>SHAPE</b>	<b>LENGTH</b>	<b>WATTS</b>
	S—Straight / 2-straps*	2-inch (5.08 cm)	9 watts
	S—Straight / 2-straps*	3-inch (7.62 cm)	9 watts
	S—Straight / 2-straps*	4-inch (10.16 cm)	13.5 watts
	S—Straight/ 3-straps*	5-inch (12.70 cm)	13.5 watts
	S—Straight/ 3-straps*	6-inch (15.25 cm)	18 watts
	L - Elbow / 2-straps*	4-inch (10.16 cm)	13.5 watts
Standard Width of wrap = 6-inch (15.25 cm) *Straps on Velcro & Snap versions only			
<b>Sensor</b>	<b>Type</b>		<b>Connector</b>
	<b>J</b> - J-Type Thermocouple <b>K</b> - K-Type Thermocouple <b>E</b> - E-Type Thermocouple <b>T</b> - T-Type Thermocouple <b>R</b> - RTD	<b>M</b> - Mini Thermocouple* (standard) <b>F</b> - Full Size Thermocouple <b>N</b> - None <b>C</b> - Custom / Special (Specify Connector P/N)	
<b>Options</b>	<b>OT</b> - 400°F (204°C) Over-Temp Cut-Off Switch		<b>Faster Type</b> <b>V</b> - Velcro <b>S</b> - Snap Fastener with Straps <b>B</b> - Boot Hook (No Straps)*

